

PGDQ2.MH17675 - MARKING AND LABELING SYSTEMS - COMPONENT

Marking and Labeling Systems - Component

See General Information for Marking and Labeling Systems - Component

SENECA LABEL, INC.

13821 Progress Pkwy
Cleveland, OH 44133-4303 USA

MH17675

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels.						
Bright Silver Mylar						
	Acrylonitrile butadiene styrene	80	-	X	-	-
	Epoxy paint	80	-	X	-	-
	Nylon - Polyamide	80	-	X	-	-
	Polyphenylene oxide/ether	80	-	X	-	-
White Gloss						
	Acrylonitrile butadiene styrene	80	-	X(dry)	-	-
	Polyphenylene oxide/ether	80	-	X(dry)	-	-
	Epoxy paint	60	-	X(dry)	-	-
	Nylon - Polyamide	60	-	X(dry)	-	-
White Hi-Gloss-OL						
	Acrylonitrile butadiene styrene	60	-	X(dry)	-	-
	Epoxy paint	60	-	X(dry)	-	-
	Nylon - Polyamide	60	-	X(dry)	-	-
	Polyphenylene oxide/ether	60	-	X(dry)	-	-
White Litho						
	Epoxy paint	80	-	X(dry)	-	-
	Acrylonitrile butadiene styrene	60	-	X(dry)	-	-
	Nylon - Polyamide	60	-	X(dry)	-	-
	Polyphenylene oxide/ether	60	-	X(dry)	-	-

White PET with Clear PET OL

	Acrylic paint	150	-40	X	X	O
	Alkyd paint	150	-40	X	X	O
	Aluminum	150	-40	X	X	O
	Chromate treated metal	150	-40	X	X	-
	Epoxy paint	150	-40	X	X	-
	Epoxy powder paint	150	-40	X	X	O
	Galvanized steel	150	-40	X	X	-
	Polyester paint (textured)	150	-40	X	X	O
	Polyester paint	150	-40	X	X	O
	Polyester powder paint	150	-40	X	X	-
	Polyurethane powder paint	150	-40	X	X	-
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	O
	Melamine	100	-40	X	X	-
	Nylon - Polyamide	100	-40	X	X	O
	Phenolic - Phenol Formaldehyde	100	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Unsaturated polyester - thermoset	100	-40	X	X	O
	Acrylonitrile butadiene styrene	80	-40	X	X	O
	Alkyd painted plastic	80	-40	X	X	-
	Epoxy	80	-40	X	X	-
	High density polyethylene	80	-40	X	X	O
	Polybutylene terephthalate	80	-40	X	X	O
	Polyethylene	80	-	X	-	-
	Polyethylene terephthalate	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polyphenylene sulfide	80	-40	X	X	-
	Polypropylene	80	-40	X	X	O
	Polystyrene	80	-40	X	X	O
	Polyvinyl chloride	80	-40	X	X	-
	Acrylic	60	-40	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

O - Occasional exposure to Lubricating Oil.

NOTE - (1) Additional characters may be added to the end of the designation after a forward slash, "/", indicating the type of release liner used unless a specific release liner is indicated. (2) Model designations may or may not include hyphens or spaces as part of the nomenclature.

Marking: Company name and model designation.

Last Updated on 2017-10-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"